



Rev	Revisions	Rev.Drawn	Date
A		Du	02.11.2010

**NOTE:**

1. MATERIAL :
  - 1-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK
  - 1-2. CONTACT : PHOSPHOR BRONZE
  - 1-3. O-RING : NBR ; COLOR : BLACK
  - 1-4. NUT : BRASS
2. FINISH :
  - 2-1. CONTACT :
    - CONTACT AREA : 10 MICRO INCHES MIN. GOLD PLATING
    - SOLDER AREA : Gold Flash
    - UNDER PLATE : NICKEL
  - 2-2. NUT : NICKEL PLATED .
3. ELECTRICAL SPECIFICATION :
  - 3-1. Rated current : 5A
  - 3-2. Voltage :125V
  - 3-3. Water proof: IPX7
4. Environmental :
  - 4-1. Operation Temperature : -20 ℃~85℃

**SST SOUTH SEA TERMINAL CO.,LTD**

SGS Report No.:	Customer:	Part No.:
		8F4P-W-E-9.2-P-2-G10-B-N
Title: M8 FEMALE SOLDER TYPE for CABLE (LONG NUTS)		
Drawn By: Storm.Li	SCALE	SHEET
Checked By: du	/	1/1
Approved By: Tony	REV.	A
	DWG NO.:	SST-101102-01
	Third angle Projection	TOLERANCE:
	General Dimension Tolerance	X. ±2MM
		.X ±0.25MM
		.XX ±0.1MM
		.XXX±0.1MM