



Rev	Revisions	Rev.Drawn	Date
A		Du	18.FEB.2013

REF 56.2

- 1. MATERIAL :**
- 1-1. HOUSING : NYLON UL94V-0 ; COLOR : BLACK
  - 1-2. CONTACT : PHOSPHOR BRONZE
  - 1-3. MAIN BODY : ZINC ALLOY
  - 1-4. LOCK SHELL : BRASS
  - 1-5. SPRING : STAINLESS
  - 1-6. ISOLATION : PVC
  - 1-7. CLAMPS : ZINC ALLOY
  - 1-8. CLAMPS BODY : ZINC ALLOY
  - 1-9. SCREW : BRASS
  - 1-10. BACK BODY : BRASS
  - 1-11. O-RING 1 : EPDM ; COLOR : BLACK
  - 1-12. GLAND : SILICONE COLOR : BLACK
  - 1-13. GLAND CAGE : POM ; COLOR : WHITE
  - 1-14. GLAND NUT : ALUMINUM ALLOY
  - 1-15. O-RING 2 : SILICONE ; COLOR : BLACK
- 2. FINISH :**
- 2-1. CONTACT : CONTACT AREA : GOLD FLASH PLATING  
SOLDER AREA : TIN  
UNDER PLATE : NICKEL
  - 2-2. MAIN BODY : NICKEL PLATED
  - 2-3. LOCK SHELL : NICKEL PLATED
  - 2-4. CLAMPS : NICKEL PLATED
  - 2-5. CLAMPS BODY : NICKEL PLATED
  - 2-6. SCREW : NICKEL PLATED
  - 2-7. BACK BODY : NICKEL PLATED
  - 2-8. GLAND NUT : SATING NICKEL PLATED
- 3. ELECTRICAL SPECIFICATION :**
- 3-1. Rated current : 5A
  - 3-2. Rated Voltage : 250V
  - 3-3. Water proof : IPX7
- 4. Environmental :**
- 4-1. Operation Temperature : -20 ℃~85℃

WP-DIN-16-3-F-W-M-2-GF-AA-SN-A    WP-DIN-16-4-F-W-M-2-GF-AA-SN-A    WP-DIN-16-5-F-W-M-2-GF-AA-SN-A    WP-DIN-16-6-F-W-M-2-GF-AA-SN-A    WP-DIN-16-7-F-W-M-2-GF-AA-SN-A    WP-DIN-16-8-F-W-M-2-GF-AA-SN-A

**SST SOUTH SEA TERMINAL CO.,LTD**

SGS Report No.:	Customer:	Part No.:
		WP-DIN-16-X-F-W-M-2-GF-AA-SN-A
Title: WATERPROOF DIN(F) ASSEMBLY TYPE		
Drawn By: Storm.Li	SCALE	SHEET
Checked By: du	1:1	1/1
Approved By: Tony	REV.	DWG NO.:
	A	/
	Third angle Projection	Units mm
	General Dimension Tolerance	
TOLERANCE:		
.x		±0.20
.xx		±0.10
.xxx		±0.05
.xxxx		±0.03
ANGULA		±1°