











Rev	Revisions	Rev.Drawn	Date
A		Du	23.SEP.2011




組裝需注意防呆位置



USB 4P (M)



1. MATERIAL :
- 1-1. EXTERNAL HOUSING : PBT UL94V-0 ; COLOR : BLACK
 - 1-2. EXTERNAL NUT : PBT UL94V-0 ; COLOR : BLACK
 - 1-3. O-RING : SILICONE ; COLOR : BROWN
 - 1-4. USB :
 - 1-4-1. HOUSING : PBT UL94V-0 ; COLOR : BLACK
 - 1-4-2. CONTACT : PHOSPHORUS BRONZE.
 - 1-4-3. SHELL : SPTe
2. FINISH :
- 2-1. CONTACT : GOLD 3u" ON CONTACT AREA
SOLDER TAILS: TIN 100u"
UNDER PLATE : NICKEL
 - 2-2. SHELL: NICKEL ON OVER ALL



扁型 O-RING(17.1*2.2*3.2)

SST SOUTH SEA TERMINAL CO.,LTD

SGS Report No.:	Customer:	Part No.:
		WP-USB-04-M-A
Title: 防水USB(M)線端		
Drawn By: Storm.Li	SCALE	SHEET
Checked By: du	1:1	1/1
Approved By: Tony	REV.	A
	DWG NO.:	QC5523
	Third angle Projection	Units
	General Dimension Tolerance	mm
	TOLERANCE:	
	.x	±0.20
	.xx	±0.10
	.xxx	±0.05
	.xxxx	±0.03
	ANGULA	±1°